

## Assembly Instructions Spider Rack #970005

### Parts List:

1. (5) Caster Wheels
2. (1) Five Leg Star Shaped Base
3. (1) Black Sleeve
4. (1) Gray Bushing
5. (1) Main Pole
6. (1) Main Rack Assembly
7. (1) 3/8" Socked Head Cap Screw
8. (1) 3/8" Flat Washer
9. (8) Black Rubber Tips

### Tools Required (not provided):

1. 3/8" Hex Key
2. Rubber Mallet

### Assembly Instructions:

1. Remove all parts from the packaging and check that they are all available for assembly
2. Place Gray Bushing (4) into Black Sleeve (3) and press into Base (2). Use rubber mallet to seat bushing assembly into the base. The bushing should protrude 1/16"-1/8" above the base.
3. Place open end of Main Pole (5) into Gray Bushing (4) and check for snug fit. If pole does not fit into gray bushing, simply turn the base over and pop the gray bushing out with a hammer and start over again at step 2. If pole is too loose, seat the bushing further in base with mallet.
4. Attach wheels (1) to base (2) assembly by pressing caster firmly into caster hole until wheels snap into place.
5. Place the rubber tips (8) on the ends of the Main Rack Assembly (6).
6. Place the Main Rack Assembly (6) on the top end of the pole with the screw hole opening and fasten with the flat washer (8) and Socket Head Cap Screw (7) using hex key.

